



Biopharmaceutical Products

C-FLEX[®]
THERMOPLASTIC ELASTOMER

C-FLEX[®] TUBING

C-FLEX[®] MOLDED ASSEMBLIES

C'EAL-FLEX[™] TUBING SEALER

TUBING FOR BIOPHARMACEUTICAL APPLICATIONS

The Material Difference

C-Flex® is a unique, patented thermoplastic elastomer specifically designed to meet the critical demands of the medical, pharmaceutical, research, biotech and diagnostics industries.

C-Flex biopharmaceutical tubing has been used by many of the world's leading biotech and pharmaceutical processing companies for over 20 years. Each coil of C-Flex tubing is extruded to precise ID, OD and wall dimensions in an FDA-registered medical device facility in accordance with the regulations governing this registration. All tubing is formulated to meet the standards of the biopharmaceutical industry and is QA tested before leaving the Saint-Gobain Performance Plastics production facility.

Physical Properties

Formulation	374	072	082
Durometer, Shore A (5 SEC. ASTM D2240)	60	60	60
Appearance	Clear	Opaque	Clear
Tensile Strength, psi (ASTM D412)	1190	1462	1190
Elongation, % (ASTM D412)	708	679	708
Tensile Modulus, @100%/300%, psi (ASTM D412)	230/380	240/360	230/380
Tensile Set, % at break	92	75	92
Tear Resistance, lb/in., Die C/Die B	175/130	180/135	175/130
Compression Set Constant Defl., "B" (22 hrs. @ 70°C), %	57	60	57
Abrasion Resistance, mg. lost/1000 cycles	9.0	5.7	9.0
Specific Gravity (ASTM D792)	0.90	0.90	0.90
Water Absorption, % at 100% RH (ASTM D570)	0.2	0.2	0.2
Brittle Point, °F (ASTM D746)	-88	-100	-88

Features

- Complies with USP 24/NF19, Class VI, FDA and USDA standards
- Manufactured under strict GMPs in an FDA-registered facility
- Non-pyrogenic, non-cytotoxic, non-hemolytic
- Chemically resistant to concentrated acids and alkalis
- Significantly less permeable than silicone
- Low platelet adhesion
- Low protein binding
- Ultra-smooth inner bore
- Available in clear or opaque formulations
- Lot traceable
- Safer disposal through incineration

Benefits

- Superior to PVC and silicone for many applications
- Longer peristaltic pump life
- Significantly fewer TOC extractables than PVC
- Heat-sealable, bondable and formable
- Remains flexible from -50°F to 275°F
- Moderate cost compared to other tubing products
- Sterilizable by radiation, ETO, autoclave or chemicals
- Available in animal-free formulations (ADCF)
- Meets FDA requirements for direct food contact

Applications

- Cell culture media
- Cell fermentation
- Diagnostic equipment
- Pharmaceutical production
- Vaccine production
- Pinch valves
- Laboratory research
- High-purity water
- Reagent dispensing
- Medical fluid/drug delivery
- Dialysis, cardiac bypass
- Botanical product production
- Peristaltic pump segments
- Sterile filling and dispensing systems



C-Flex® Biopharmaceutical Tubing Product Selection Guide

Chemical Compatibility

- Acids, dilute/weak – acceptable
- Acids, strong/concentrated – acceptable
- Bases, dilute/weak – acceptable
- Bases, strong/concentrated – acceptable
- Salts – acceptable
- Alcohols – not recommended
- Milk products (<4% fat) – acceptable
- Organic solvents – not recommended
- Oil/Water emulsions – test

Product Profile

C-Flex® biopharmaceutical tubing is part of a family of C-Flex products that includes micro-bore tubing, tight tolerance pump tubing, medical-grade tubing, commercial-grade tubing and custom tubing formulations from 50A to 80A Durometer. An extensive database of C-Flex bio-compatibility data is available to assist in the validation of C-Flex for your application. Contact Saint-Gobain Performance Plastics at (800) 541-6880 and ask for the Regulatory Affairs Department to request access to this data and the FDA Master Files.

CPT Tubing Catalog # (1)	Packaging Options (2)	ID x OD x Wall (in decimals)	ID x OD (in fractions)
xxx-125-2	C50, S	.125 x .250 x .062	1/8 x 1/4
xxx-188-2	C50, S	.188 x .313 x .062	3/16 x 5/16
xxx-188-3	C50, S	.188 x .375 x .094	3/16 x 3/8
xxx-250-2	C50, S	.250 x .375 x .062	1/4 x 3/8
xxx-250-3	C50, S	.250 x .438 x .094	1/4 x 7/16
xxx-250-4	C50, S	.250 x .500 x .125	1/4 x 1/2
xxx-313-3	C50, S	.313 x .500 x .093	5/16 x 1/2
xxx-375-2	C50, S	.375 x .500 x .062	3/8 x 1/2
xxx-375-3	C50, S	.375 x .563 x .094	3/8 x 9/16
xxx-375-4	C50, S	.375 x .625 x .125	3/8 x 5/8
xxx-500-3	C50, S	.500 x .688 x .094	1/2 x 5/8
xxx-500-4	C50, S	.500 x .750 x .125	1/2 x 3/4
xxx-625-4	C50	.625 x .875 x .125	5/8 x 7/8
xxx-750-4	C15	.750 x 1.00 x .125	3/4 x 1
xxx-750-6	C15	.750 x 1.125 x .188	3/4 x 1-1/8
xxx-750-8	C15	.750 x 1.250 x .250	3/4 x 1-1/4
xxx-1000-6	C15	1.00 x 1.375 x .188	1 x 1-3/8
xxx-1000-8	C15	1.00 x 1.500 x .250	1 x 1-1/2
(1) FORMULAS: (xxx)		(2) PACKAGING OPTIONS	
082 – Clear, 60A Durometer		C50 – 50' Coils	
374 - Clear, 60A Durometer ADCF		C15 – 15' Coils	
072 – Opaque, 60A Durometer		S - Bulk spools are available for OEM product applications	
C-Flex is available through Authorized Distributors ONLY. Contact the Customer Service Department at (800) 541-6880 for the name of the authorized C-Flex distributor in your area.			

C'eal-Flex™ – TPE Ultra Sealer

SYSTEM DESCRIPTION

The **C'eal-Flex™** TPE Ultra Sealer measures 7" x 9" x 4" (18 x 25 x 10 cm), weighs 6.5 lbs and operates from regular 110-volt current and filtered air. It offers simple one-button operation and computer-controlled, adjustable sealing temperature and dwell times. The unit is easy to clean, portable and compact. One of the Remote Sealing Heads with 10-ft cable is required.

SYSTEM PRICING

Product	Catalog Number
C'eal-Flex Base Generator/Control Unit 9" x 7" x 4" Includes both electric and pneumatic connectors	150-007-001
Thin Wall Remote Sealing Head with 10-ft cable. Seals thin wall (.062) tubing: .125 OD - .375 OD.	150-009-001
Thick Wall Remote Sealing Head with 10-ft cable. Seals thick wall (.125) tubing: .375 OD - .750 OD.	150-010-001

For more than four decades, Saint-Gobain Performance Plastics and its family of companies have supplied the world with innovative, high-performance polymer products for the most demanding applications. Our tradition of excellence goes back more than 300 years through our parent company, Compagnie de Saint-Gobain, one of the world's top 100 industrial corporations, with operations in more than 40 countries. This successful corporation has been built with the single purpose of serving the customer and a commitment to quality and leadership in each of the industries served.



BIOPHARMACEUTICAL PRODUCTS MANUFACTURING FACILITIES

Saint-Gobain Performance Plastics
4451 110th Avenue North
Clearwater, FL 33762
Tel: (800) 541-6880
Tel: (727) 531-4191
Fax: (727) 530-5603

Saint-Gobain Performance Plastics
2664 Gilchrist Road
Akron, OH 44305
Tel: (800) 798-1554
Tel: (330) 798-9240
Fax: (330) 798-6968

Saint-Gobain Performance Plastics
3910 Terry-Diane Street
Beaverton, MI 48612
Tel: (888) 387-0067
Tel: (989) 435-9533
Fax: (989) 435-2355

Saint-Gobain Performance Plastics
460 Milltown Road
Bridgewater, NJ 08807
Tel: (800) 435-3992
Tel: (908) 218-8888
Fax: (908) 218-9009

Saint-Gobain Performance Plastics
700 Warner Blvd.
Taunton, MA 02780
Tel: (800) 722-7106
Tel: (508) 823-7701
Fax: (508) 823-1438

Saint-Gobain Performance Plastics
La Mothe-aux-Aulnaies
F-89120 Charny, France
Tel: (33) 3-86-63-78-78
Fax: (33) 3-86-63-77-77

Saint-Gobain Performance Plastics
Norton KK
10801-5, Haramura, Suwa-gun
Nagano 391-0106 Japan
Tel: (81) 266-79-6400
Fax: (81) 266-70-1001

Consult a Saint-Gobain Performance Plastics Sales Representative for the product and material formulation that best suits your specific application needs.

WWW.BIOPHARM.SAINT-GOBAIN.COM

*C'eal-Flex™ is a trademark.
C-Flex® is a registered trademark.*

WARNING: The content of Saint-Gobain tubing materials is not certified by the FDA for implant devices and is neither designed nor intended to be used in medical applications involving permanent implantation in the human body or permanent contact with body fluids or tissues. Failure to comply with this warning may lead to serious bodily injury or death.

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain Performance Plastics materials for all intended uses. Laboratory, field or clinical tests must be conducted in accordance with applicable requirements in order to determine the safety and effectiveness for use of materials in any particular application. If intended for medical use, it is the user's responsibility to ensure that the materials to be used comply with all applicable medical regulatory requirements.

Limitation of Liability: Except for products for which Saint-Gobain Performance Plastics (SGPPL) has established a specific written warranty, the products described herein are sold by SGPPL without any guarantee and/or warranty, oral or written. User assumes all risk, if any, including the risk of injury, loss or damage, whether direct, consequential or incidental, arising out of the use, misuse or inability to use these products.

SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product or of any final product into which the product may be incorporated by the purchaser and/or user.